



► **Single Row Sealed Series**

It is sealed single row spherical roller bearing. Single-row of large rollers result in increased dynamic load capacity and up to 100% greater misalignment of conventional double row spherical roller bearings. Sealing features are combined with the lip-wiping sealing function of an added contact seal, for applications where contamination conditions are particularly severe or where substantial amounts of moisture are present.

SB系列轴承采用单列球面滚子设计，具有更好的抗震性和轴向承载力；迷宫式密封片和卡簧设计确保了良好的密封性和透气性，实现更好的润滑效果。外型尺寸与普通调心滚子轴承一致，可互用。

Bearing Number	Principal dimensions (mm)			Weight(Kg)
型号	基本尺寸 (mm)			重量
	d	D	B	
SB-22205-W33-SS	25	52	18	0.18
SB-22206-W33-SS	30	62	20	0.28
SB-22207-W33-SS	35	72	23	0.43
SB-22208-W33-SS	40	80	23	0.52
SB-22209-W33-SS	45	85	23	0.58
SB-22210-W33-SS	50	90	23	0.68
SB-22211-W33-SS	55	100	25	0.85
SB-22212-W33-SS	60	110	28	1.83
SB-22213-W33-SS	65	120	1	1.63
SB-22214-W33-SS	70	120	31	1.83
SB-22215-W33-SS	75	130	31	1.63
SB-22217-W33-SS	85	150	36	3.00
SB-22218-W33-SS	90	160	40	3.70
SB-22219-W33-SS	95	170	43	4.30
SB-22220-W33-SS	100	180	46	5.00
SB-22222-W33-SS	110	220	53	7.40
SB-22224-W33-SS	120	225	58	9.20
SB-22308-W33-SS	40	90	33	1.35
SB-22309-W33-SS	45	110	36	1.41