

轴承代号	基本尺寸				基本额定载荷		极限转速		其他尺寸					安装相关尺寸			重量
	d	D	T	rmin	Ca	COa	脂润滑	油润滑	d1	D1	B	C	A	damin	Da max	rg max	
	mm				KN		r/min		mm					mm			kg
29414/YAD	70	150	48	2.3	314	430	1400	2000	103	135	31	23	44	105	125	2	3.87
29416/YAD	80	170	54	2.5	407	550	1100	1700	117	155	35	25	50	120	141	2	5.33
29418/YAD	90	190	60	2.5	484	690	950	1500	132	170	39	29	56	135	158	2	7.13
29420/YAD	100	210	67	3	644	865	850	1300	146	190	45	32	62	150	175	2.5	10.5
29324/YAD	120	210	54	2.5	418	650	1000	1600	161	188	34	30	57	160	181	2	6.88
29424/YAD	120	250	78	3.7	781	1060	750	1100	181	222	48	38	74	180	209	3	19.5
29424/YAD-1	120	250	78	2.5	781	1060	750	1100	181	222	48	38	74	180	209	2.5	19.4
29326/YAD	130	225	58	3.7	484	750	950	1500	170	200	37	29	76	175	194	2	8.26
29429/YAD	130	270	85	3.7	836	1100	700	1100	190	240	55	44	79	195	227	3	23
29428/YAD	140	280	85	3.7	908	1120	670	950	203	247	55	47	64	205	236	3	22.7
29430/YAD	150	300	90	4.7	1090	1710	630	900	220	270	60	48	69	220	253	3	27.3
29432/YAD	160	320	95	4.7	1100	1720	560	800	234	275	61	53	74	235	270	4	33.3
29434/YAD	170	340	103	3	1330	2130	530	750	243	310	71	48	104	250	286	3	40.7
29336/YAD	180	300	73	4.7	974	3000	630	900	230	276	50	35	103	235	262	2.5	19.4
29436/YAD	180	360	109	2	1330	2130	750	750	265	308	67	58	82	265	304	2	42.3
29244/YAD	220	300	48	6	484	910	850	1300	260	286	31	24	117	260	273	2	7.92
29448/YAD	240	440	122	3.7	2110	3550	750	750	330	400	78	59	142	335	378	3	74.5
29252/YAD	260	360	60	2.1	798	1550	530	750	302	335	38	30	139	310	326	2	15.7
29356/YAD	280	440	95	5	1600	6060	530	750	348	413	64	46	158	355	390	4	49.1
29268/YAD	340	460	73	3	1250	2440	530	750	388	438	48	36	204	400	422	2.5	31.4
29284/YAD	420	580	95	4.7	2060	4150		560	489	548	62	46	251	500	525	4	78.9
294/500/YAD	500	870	224	9.5	6930	27700		340	654	760	140	108	290	685	755	8	462

292/630YAD	630	850	132	6	3580	8350		300	728	800	86	65	338	740	780	5	231
292/710/YAD	710	950	145	6	3960	12000		240	805	895	92	75	380	820	880	5	279
294/750/YAD	750	1280	315	15	14850	31000		100	972	1152	160	158	448	1015	1120	12	1340